



PROJECT		TECHNICAL INFORMATION	
LIGHTING CODE		CONNECTED LOAD (W)	20W
MODEL	ARROVO LUX150	LUMEN OUTPUT (lm)	1900lm
DESCRIPTION	Recessed LED downlight. Material made of die-cast powder coated aluminum with anodized aluminum specular silver reflector. Complete with electronic LED Driver.	LUMINOUS EFFICACY	95lm/w
ORIGIN	Asia	COLOR TEMPERATURE	<input type="radio"/> 3000K <input type="radio"/> 4000K
FINISHES	<input checked="" type="checkbox"/> White <input type="checkbox"/> Black <input type="checkbox"/> Aluminium	COLOR RENDERING INDEX	80
LOCATION		BEAM ANGLE	60Degree
		DIMENSION	(L) Ø 150mm (W) (H) 123mm
		DRIVER	<input checked="" type="checkbox"/> REMOTE <input type="checkbox"/> INTEGRATED <input type="checkbox"/> DALI <input type="checkbox"/> 1-10 V <input checked="" type="checkbox"/> ON-OFF <input type="checkbox"/> ES LAMP

ILLUSTRATIONS



COB LED CRI≥80 IP44 CE RoHS



	h(m)	D(m)	Em(lx)	E _{max} (lx)	
	1	1.1	681	1514	
	2	2.2	208	379	
	3	3.3	109	168	
	4	4.4	71	95	
	5	5.5	52	61	