

PROJECT	TECHNICAL INFORMATION	
LIGHTING CODE	CONNECTED LOAD (W) 15W	
MODEL	LUMEN OUTPUT (lm) 1300lm	
DESCRIPTION	LUMINOUS EFFICACY 87lm/w	
	COLOR TEMPERATURE <input type="radio"/> 3000K <input type="radio"/> 4000K	
	COLOR RENDERING INDEX 80	
	BEAM ANGLE	
ORIGIN	DIMENSION (L) Ø 110mm <b>Cutout:</b>	
	(W) 102mm	
FINISHES	(H) 115mm	
	DRIVER <input checked="" type="checkbox"/> REMOTE	
LOCATION	<input type="checkbox"/> INTEGRATED	
	<input type="checkbox"/> DALI	
	<input type="checkbox"/> 1-10 V	
	<input checked="" type="checkbox"/> ON-OFF	
	<input type="checkbox"/> ES LAMP	

Arrovo Gamma-A

Recessed mounded adjustable LED Downlight with round construction. Material made of die-cast aluminium housing, UGR<10 silver mirror reflector UGR<10, split structure for easy maintenance. Complete with remote electronic LED Driver.

Asia

White  Black  Aluminum

### ILLUSTRATIONS

	
	