

PROJECT		TECHNICAL SPECIFICATION	
LIGHTING CODE		CONNECTED LOAD (W)	40W
MODEL	ARROVO PL600-40W-4000K-WH	LUMEN OUTPUT (lm)	3200lm
	Recessed lay-in LED luminaire with opal cover. For system ceilings with exposed grids. Version M73, system dimension 595x595 mm. Luminaire body of aluminium. Equipped with remote electronic LED Driver..	LUMINOUS EFFICACY	80lm/W
ORIGIN	Asia	COLOR TEMPERATURE	<input type="radio"/> 3000K <input checked="" type="radio"/> 4000K
FINISHES	<input checked="" type="radio"/> White <input type="radio"/> Black <input type="radio"/> Aluminium	COLOR RENDERING INDEX	90 UGR
LOCATION		BEAM ANGLE	Wide IP Rate: 40
		DIMENSION	(L) 595mm (W) 595mm (H) 9mm
		DRIVER	<input checked="" type="radio"/> REMOTE <input type="radio"/> INTEGRATED
		FEATURE	<input type="radio"/> DALI <input type="radio"/> 1-10 V <input checked="" type="radio"/> ON-OFF <input type="radio"/> ES LAMP

ILLUSTRATIONS



		Consultant/Client Approval:			
		Approve	Approve with comment	Not Approve; to resubmit	
		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
Comment:					
Signed:					